



# HOSHIZAKI ICE MACHINES

## KM-30A

### Product Features

- Individual premium crescent ice 30mm x 37mm x 13mm
- Satin stainless steel front panel
- Slide in cleanable air filter
- Durable injection moulded front Louver
- Air flow-front intake and exhaust-can be built in
- Standard control box across the range
- Stainless steel evaporator
- Vertical pump motor-no mechanical seals
- Domed float switch-good in hard water areas
- Snap in water tank design-easy to remove for sanitation
- Has low electrical consumption
- Has low water consumption
- High production capacity



### Range

- KM-30A
- KM-50A
- KM-75A



## Product Specifications

- **Dimensions**

Width: 450 mm  
Depth: 610 mm  
Height: 840 mm

- **Weight**

Net: 39kg  
Packed: 49kg

- **AC Supply Voltage**

220-240V/50Hz, 10AMPs

- **Condenser**

Air Cooled

- **Refrigerant**

R134A

- **Ambient**

1°C - 40°C

- **Water Temp & Pressure**

5°C - 35°C/70kpa - 800kpa

- **Ice Production per 24 hours**

Air temp: 10°C Water temp: 10°C - approx 36kg  
Air temp: 21°C Water temp: 15°C - approx 32kg  
Air temp: 32°C Water temp: 21°C - approx 25kg

- **Freeze Cycle**

30 minutes

- **Ice Production per Cycle**

.71kg/80pcs

- **Maximum Storage Capacity**

16kg

- **Accessories**

Instruction Manual  
Scoop  
Installation Kit  
Adjustable Bolt  
Outlet Hose

