



HOSHIZAKI ICE MACHINES

KM-50A

Product Features

- Individual premium crescent ice 30mm x 37mm x 13mm
- Satin stainless steel front panel
- Slide in cleanable air filter
- Durable injection moulded front Louver
- Air flow-front intake and exhaust-can be built in
- Standard control box across the range
- Stainless steel evaporator
- Vertical pump motor-no mechanical seals
- Domed float switch-good in hard water areas
- Snap in water tank design-easy to remove for sanitation
- Has low electrical consumption
- Has low water consumption
- High production capacity



Range

- KM-30A
- KM-50A
- KM-75A



Product Specifications

- Dimensions**

Width: 603mm
Depth: 610mm
Height: 840mm

- Weight**

Net: 46kg
Packed: 58kg

- AC Supply Voltage**

220-240V/50Hz, 10AMPs

- Condenser**

Air Cooled

- Refrigerant**

R134a

- Ambient**

1°C - 40°C

- Water Temp & Pressure**

5°C - 35°C/70kpa - 800kpa

- Ice Production per 24 hours**

Air temp: 10°C Water temp: 10°C - approx 52kg
Air temp: 21°C Water temp: 15°C - approx 50kg
Air temp: 32°C Water temp: 21°C - approx 41kg

- Freeze Cycle**

25 minutes

- Ice Production per Cycle**

.95kg/110pcs

- Maximum Storage Capacity**

23kg

- Accessories**

Instruction Manual
Scoop
Adjustable Bolt
Outlet Hose

